









iColor® 350 SYSTEM SPECIFICATIONS

Up to 20 ppm 350 MHz Print Speed: Processor

Up to 30,000 pg/mo. Duty Cycle: Duplex: Standard

256 MB RAM Memory: Up to 2400 x 600 dpi Resolution:

CL6c/5c, PostScript3 emulation, PictBridge 3^{TM} 1.5" - 8.375" (38mm - 212mm) Media Types:

Emulation:

Windows® Vista, Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008/R2, Windows® Server 2012/R2; Macintosh OS X Native V10.9-10.12; Linux; Unix Filter 10Base-T/100Base-TX, IEEE 802.11b/g/n, NFC Tag, USB 2.0 High speed Type A [For Pictbridge, Scan to USB Flash Drives] Operating Systems:

Paper Cassette: 250-sheet Legal/Letter/Universal

Paper Sizes (Min./Max.): A4, A5, A6, B5, B6, Legal, Letter, HLT, Executive, F, Foolscap, Folio,

Custom size: (Min.) 90 x 148 mm, (Max.) 216 x 356 mm

Standard Tray: 60 - 160 g/m; Optional Tray: 60 - 105 g/m; Bypass: 60 - 160 g/m; Duplex: 60 - 90 g/m

15.8" x 17.7" x 12.6" (40 cm x 45 cm x 32 cm)

62.4 lb. (28.3 kg)

Paper Weight: Size: (WxDxH):

Weight:

Power Models: 120v & 220v models available

SYSTEM INCLUDES

Interfaces:

• The iColor® 350 comes standard with four dye sublimation toner cartridges for full color CMYK



